


Heavy type Plastic conduit systems (1250Nt)

CONDUR® ISR Bend



RAL 7035



Application Standards

EN 61386.21

Patents protected

1009810, EP2698792, 1010513



Properties

Resistance to impact	6J (at -25°C)
Resistance to compression	1250(Nt)
Temperature range	-25°C to +60°C
IP ingress protection	min IP65
Ageing resistance	UV stabilized
Rodent repellent	Not attractive to rodents
Raw material	Heavy metals free (RoHS), specially stabilized thermoplastic U-PVC
Electrical characteristics	With electrical insulated characteristics
Resistance to flame propagating	Non flame propagating
Antistatic Technology	Protection against static electricity
Antiscratch Technology	Protection against scratching from cable routing
Marking	Engraved with laser printing

Note: Bends packaging do not contain coupler.

Type	Part number						
Ø16	4038016	16	12.1	27	59	10	480
Ø20	4038020	20	16.0	35	74	10	480
Ø25	4038025	25	20.9	36.7	108	10	240
Ø32	4038032	32	27.4	47.6	142	6	48
Ø40	4038040	40	35.1	52.9	144	6	84
Ø50	4038050	50	44.7	62	175	4	40
Ø63	4038063	63	57.2	77	203	4	24

