


Medium type Plastic conduit systems (750Nt)

DUROSOL® PLUS ISR Junction box with seals



RAL 9004



Application Standards
EN 60670-22

Patents protected
1010513



Properties

Box raw material	PO blend
Temperature range	-25°C to +60°C
Electrical characteristics	With electrical insulated characteristics
Resistance to flame propagating	Non flame propagating
Number of entries	7
Kind of entries	Plug in seals
Ingress protection	IP 55
Number of base knock outs	4
Conduit alignment	Yes
Condensation opening	Yes
Flame retardant	650°C
Voltage	800V
Halogen free	No toxic gases in case of fire
Low acidity	No corrosive gases in case of fire
UV stability	Yes
Antistatic Technology	Yes
Antiscratch Technology	Yes

* Cover plate and plug in seals are made of PE

Watertight due to its elastic and directly mounted cover plate.

Junction boxes with seals: These boxes are provided with plug in seals for easy positioning of cables, without the use of additional fittings, after cutting at the pre-marked points. DUROSOL PLUS adaptors, of different diameters, can be easily fastened in the openings after pushing out the plug in seals.



Type	Part number	A mm	B mm	C mm		
Ø16/20	3025016	67	38	21.6	10	280
Ø20/16	3025020	82	43	21.6	10	160
Ø25/32	3025025	101	51	35.1	5	100